

TECHNICAL SPECIFICATIONS

GNSS Performance ⁽¹⁾

Channels	1608 channels
GPS	L1C/A/L2P(Y)/L2C/L5
GLONASS	L1, L2
Galileo	E1, E5a, E5b, E6*
BeiDou	B1I, B2I, B3I, B1C, B2a, B2b
QZSS	L1, L2, L5, L6*
PPP	B2b-PPP
SBAS	L1, L2

GNSS Accuracies ⁽²⁾

Real time kinematics (RTK)	Horizontal: 8 mm + 1 ppm RMS Vertical: 15 mm + 1 ppm RMS Initialization time: < 10 s Initialization reliability: > 99.9%
Post-processing kinematics (PPK)	Horizontal: 3 mm + 1 ppm RMS Vertical: 5 mm + 1 ppm RMS
Post-processing static	Horizontal: 2.5 mm + 0.5 ppm RMS Vertical: 5 mm + 0.5 ppm RMS
Code differential	Horizontal: 0.4 m RMS Vertical: 0.8 m RMS
Autonomous	Horizontal: 1 m RMS Vertical: 1.5 m RMS
Positioning rate	Up to 10 Hz
Time to first fix ⁽³⁾	Cold start: < 45 s Hot start: < 30 s Signal re-acquisition: < 2 s

Hardware

Size (L x W x H)	Φ 160.5 mm × 103mm (Φ 6.32 in × 4.06 in)
Weight	1.73 kg (3.81 lb)
Environment	Operating: -40 °C to +65 °C (-40 °F to +149 °F) Storage: -40 °C to +85 °C (-40 °F to +185 °F)
Humidity	100% condensation
Ingress protection	IP67 waterproof and dustproof, protected from temporary immersion to depth 1m
Shock	Survive a 2-meter pole drop
Front panel	2 LED 0.96" OLED Display

Communication

Network modem	Integrated 4G modem LTE (FDD): B1, B2, B3, B4, B5, B7, B8, B20 DC - HSPA+/HSPA+/HSPA/UMTS: B1, B2, B5, B8 EDGE/GPRS/GSM850/900/1800/1900MHZ
Wi-Fi	802.11 b/g/n, access point mode
Bluetooth®	BT4.1
Others	NFC
Ports	1 x 7-pin LEMO port (external power, RS -232) 1 x UHF antenna port (TNC female)
UHF radio ⁽⁴⁾	Standard Internal Rx/Tx: 450 - 470 MHz Transmit Power: up to 5 W Protocol: EFIX, Transparent, TT450, Satel Link rate: 9600 bps / 19200 bps Range: Typical 15 km with FarRadio, up to 25km with optimal conditions
Data formats	RTCM2.x, RTCM3.x, CMR input / output RINEX2.11, 3.02 NMEA 0183 output NTRIP Client, NTRIP Caster
Data storage	8 GB memory

Electrical

Power consumption	12 W (depending on user settings)
Li-ion battery capacity	2 x 7000 mAh, 7.4 V
Operating time on internal battery ⁽⁵⁾	UHF receive / transmit (5 W): 8 h to 12 h Static: up to 15 h
External power input	9 V DC to 28 V DC

*All specifications are subject to change without notice.

(1) Compliant, but s subject to availability of BDS ICD and Galileo commercial servicedefinition.Galileo E6 and QZSS L6 will be provided through future firmware upgrade.

(2) Accuracy and reliability are determined under open sky, free of multipaths, optimalGNSS geometry and atmospheric condition. Performances assume minimum of 5satellites, follow up of recommended general GPS practices.

(3) Typical observed values.

(4) The use of UHF datalink may be subject to local regulations. Users must ensure thatthe device is not operated without the permission of the local authorities on frequencies orpower output other than those specifically reserved and intended for use without requiredpermit. Compliant and Satel protocol to be provided through future firmware upgrade.

(5) Battery life is subject to operating temperature.



EFIX Geomatics Co., Ltd.

Room 1137, D, 11/F, Building 1, No. 158 Shuanglian Road, Qingpu District, Shanghai
+86 150 2100 7664
Sales@efix-geo.com
www.efix-geo.com



RUGGED VERSATILE GNSS BASE STATION

5 W Built-in UHF **15 km** Coverage **12 H+** Operating Time

The eBase GNSS receiver is an integrated professional GNSS base station designed to meet the specific needs of surveyors working in UHF base-rover mode.

The integrated UHF radio, low power consumption and long life eliminates the need for heavy external batteries, bulky cables, external radios and radio antennas. Compared to standard external radio modems, the eBase UHF base station offers outstanding performance with wide coverage and long operating times.

Its 5-watt radio module provides up to 15 km of GNSS RTK operating range and over 12 hours of battery life without battery changes. In addition, the eBase features real-time UHF interference self-testing technology, allowing surveyors to select the most appropriate frequency channel for use.

INTEGRATED AND PORTABLE GNSS BASE SOLUTION

- Easy to carry, reducing overall package weight by over 70%.
- Easy to set up, get started in the field at least 3 times more efficiently.
- Integrated 5W UHF and 4G modem for multi-mode RTK corrections transmission via UHF and TCP/IP services.

BROADER COVERAGE AND LONGER DURATION

- Low power consumption, in a typical survey operation the 5W FarRadio UHF modem can operate for over 12 hours with 15km coverage.
- In more challenging surveys, such as forests and suburban areas, coverage can be up to 5 km.
- In open areas coverage can reach up to 25 km.

1608-CHANNEL GNSS AND MULTI-CONSTELLATIONS ALGORITHMS

- Provide full GPS + GLONASS + Galileo + BeiDou + QZSS constellation tracking, even in harsh environments.
- Output standard DGNSS corrections in RTCM 3.x format for optimum performance.
- 8 GB internal memory to store GNSS raw data for post-processing or quality control.

RUGGED DESIGN FOR UNINTERRUPTED WORK

- Designed to meet stringent IP67 standards for water and dust resistance.
- Magnesium-aluminium body for reduced weight and increased durability.
- Can withstand a 2-meter drop to a hard ground.